

Contact Us About 3M Search 3M 3M Worldwide

Select a Location > English >

3M Worldwide : Australia : Utilities and Telecommunications

<u>Product Catalogue for Telecommunication Access Products</u> > <u>Related Products</u> > <u>Static Control Testers</u> >

3M™ Wrist Strap And Footwear Tester, 740



The 3M Wrist Strap And Footwear Tester 740 Is An Ac-Powered Unit Designed To Be Wall-Mounted In A Production Facility For Daily Testing Of Employees? Static Control Wrist Straps.

[click to enlarge]


3M Order Code: 98-0798-2525-7 Bar Code: 0 00 51138 37598 0

740 Properties

Item	Properties
Dimensions	5.43 in. x 7.48 in. x 2.09 in. (13,8 cm x 19,0 cm x 5,3 cm)
Weight	15.75 oz. (450 gm)
Power Supply	27 volt DC transformer, 150 mA (AC/DC adapter suplied) 6 ft. (1,8 m) wire
Test Voltage	20 volts DC, ± 1 volt (open circuit)
Resistance Ranges	Lower limit: 750K ohms
Upper limit wrist strap	2, 5, 10 and 35M ohms
Upper limit footwear	10, 35, 50 and 100M ohms
Accuracy	+ 20%, -0% for 750K ohms lower limit ±10% for 2M, 5M, 10M, 35M and 50M ohms ±20% for 100M ohms
Output	Open collector at pins 1, 2, 4 and 5. DC return at pin 5. +5 volts at pin 3.
Wall Mounting	3M™ Dual Lock™ System.

Additional Information

Use of the optional 3M™ Shoe Electrode 741 attachment allows the tester to be used as a footwear tester as well. The optional Shoe Electrode 741 is a test plate that connects to the Wrist Strap and Footwear Tester 740.



Characteristics

EPC Can ViewPublicHeight2.09 InchLength7.48 InchWall MountableYes

1 of 2 17/04/2009 12:46

Weight 15.75 Ounce Width 5.43 Inch

©3M 1995-2006 Legal Information Privacy Policy Contact Us About 3M Search 3M 3M Worldwide

2 of 2